CLAIM LISTING

This listing of claims will replace all prior versions, and listings of claims in the application:

IN THE CLAIMS

- 1-25. (canceled)
- 26. (previously presented) A programmable logic device comprising: a plurality of resources logically subdivided into a plurality of programmable logic blocks;
 - a first voltage supply terminal configured to receive a first supply voltage; and
- a plurality of first switch elements, wherein each first switch element is coupled between one of the programmable logic blocks and the first voltage supply terminal.
- 27. (original) The programmable logic device of Claim 26, further comprising:
 - a second voltage supply terminal configured to receive a second supply voltage; and
 - a plurality of second switch elements, wherein each second switch element is coupled between one of the programmable logic blocks and the second voltage supply terminal.
- 28. (original) The programmable logic device of Claim 26, further comprising a control circuit coupled to the plurality of first switch elements, wherein the control circuit is configured to provide a plurality of control signals for controlling the plurality of first switch elements.

X-1462 US PATENT 10/666,668 Conf. No. 8241

29. (original) The programmable logic device of Claim 28, wherein the control circuit comprises a plurality of configuration memory cells configured to store a corresponding plurality of configuration data values, wherein the control circuit provides the plurality of control signals in response to the plurality of configuration data values.

- 30. (original) The programmable logic device of Claim 29, wherein the control circuit further comprises a plurality of user control terminals configured to receive a corresponding plurality of user control signals, wherein the control circuit further provides the plurality of control signals in response to the plurality of user control signals.
- 31. (original) The programmable logic device of Claim 28, wherein the control circuit comprises a plurality of user control terminals configured to receive a corresponding plurality of user control signals, wherein the control circuit provides the plurality of control signals in response to the plurality of user control signals.
- 32. (original) The programmable logic device of Claim 26, wherein each first switch element comprises a transistor.
 - 33. (withdrawn) A programmable logic device comprising:
 a first voltage supply terminal configured to receive a first supply voltage;
 a plurality of programmable logic blocks, each programmable logic block
 comprising one or more resources of the programmable logic device; and
 a plurality of voltage regulators, wherein each voltage regulator is
 coupled between one of the programmable logic blocks and the first voltage
 supply terminal.

X-1462 US PATENT 10/666,668 Conf. No. 8241

34. (withdrawn) The programmable logic device of Claim 33, further comprising a control circuit coupled to each of the voltage regulators, wherein the control circuit is configured to provide a plurality of control signals for controlling the plurality of voltage regulators.

- 35. (withdrawn) The programmable logic device of Claim 34, wherein the control circuit comprises a plurality of configuration memory cells configured to store a corresponding plurality of configuration data values, wherein the control circuit provides the plurality of control signals in response to the plurality of configuration data values.
- 36. (withdrawn) The programmable logic device of Claim 35, wherein the control circuit further comprises a plurality of user control terminals configured to receive a corresponding plurality of user control signals, wherein the control circuit further provides the plurality of control signals in response to the plurality of user control signals.
- 37. (withdrawn) The programmable logic device of Claim 34, wherein the control circuit comprises a plurality of user control terminals configured to receive a corresponding plurality of user control signals, wherein the control circuit provides the plurality of control signals in response to the plurality of user control signals.